

Powerful Workforce Management Terminal



Fully Customizable, Secure, Water and Dust proof.



Workforce data collection Integration Flexibility



Specifications

| Features | Technical Specifications |
|---------------|--|
| Processor | 8 core processor |
| Display | <ul style="list-style-type: none">7" TFT LCD Capacitive Touch Screen1024 x 600 Resolution16:9.6 Aspect Ratio |
| System | Android 10 |
| Memory | 2GB RAM, 16GB ROM, micro SDcard slot |
| Capacity | Fingerprint Module: 20,000 FAM33 Face Module: Visible light - 20,000, Near-infrared - 6,000 FAM33 Palm Module: Visible light - 5,000 Card: 10,000 Transaction: 1 Million |
| Communication | <ul style="list-style-type: none">Standard 10/100/1000 Mbps EthernetCertified Wi-Fi Dual Band 2.4G/5G, 802.11 a/b/g/n/acUSB 2.0 PortsWiegandPTCRB Certified 4G LTE |
| Interface | <ul style="list-style-type: none">LED module: 1AUX Input: 2Wiegand Input: 2Programmable LED indicator: 2 |
| Environment | Operating Temperature: 14° F to 131° F (-10° C to 55° C) Operating Humidity: 5% to 80% non-condensing |
| Dimensions | Width Base: 9.21 in. (23.4cm) Width fully configured: 9.72 in. (24.7cm) Height: 5.28 in. (13.4cm) Depth: 2.38 in. (6.05cm) |

| Features | Technical Specifications |
|---------------------------------------|---|
| Biometric Technology | FP (ZK): Touch-based optical fingerprint reader Facial: Infrared light facial biometric that can identify user under 1 second. Visible Light Recognition: V5.9 with FAM33 Module Palm: FAM33 Module - Palm Support, Visible Light |
| Audio | Speaker, Microphone |
| Soft Keypad | Capacitive Touch Screen |
| Readers & Supported Card Technologies | RFID: EM4100 SERIES PROX CARDS <ul style="list-style-type: none">PASSIVE PROX/RFID responderMulti-frequency card reader, UltiCard supports all major RFID standards-for frequency ranges 125/134.2kHz and 13.56MHz, including NFC |
| Power | AC Power Adaptor: 12 V, 1.5A PoE (Power over Ethernet): PoE+ IEEE 802.3 at Power Class Levels: 0~4 Maximum Current: 720mA Voltage Range(at PSE): 50~57VDC Maximum Power(at PES): 30W Input Voltage (at PD): 48V Maximum Power (at PD): 30W Battery: Voltage: 7.4 V Capacity: 7600mAh Charge Voltage: 8.4V Normal Charge: 8hrs Fast Charge: 5hrs |

