


Next-Generation 7-inch flexible time clock

With new Innovative facial and biometric technology.

Workforce data collection
Integration Flexibility



Specifications

Features	Technical Specifications
Processor	8 core processor
Display	<ul style="list-style-type: none"> 7" TFT LCD Capacitive Touch Screen 1024 x 600 Resolution 16:9.6 Aspect Ratio
Operating System	Android
Memory	2GB RAM, 16GB ROM, micro SDcard slot
Capacity	Fingerprint Module: 20,000 FAM33 Face Module: Visible light - 20,000, Near-infrared - 6,000 Card: 10,000 Transaction: 1 Million
Communication	<ul style="list-style-type: none"> Standard 10/100/1000 Mbps Ethernet Certified Wi-Fi Dual Band 2.4G/5G, 802.11 a/b/g/n/ac USB 2.0 Ports Wiegand
Interface	<ul style="list-style-type: none"> AUX Input: 2 Wiegand Input: 2 Relay: 2 (Alarm, Bell, External Lock) Programmable LED indicator: 2
Environment	Operating Temperature: 32° F to 113° F (0° C to 45° C) Operating Humidity: 5% to 80% non-condensing
Dimensions	Width Base with Cover Plate: 7.75 in. (19.6 cm) Width Fully Configured: 12.325 in. (31.3cm) Height: 5.675 in. (14.4.9 cm) Depth: 3 in. (7.52 cm) Weight: 2.9 lbs. (1.3 kg)

Features	Technical Specifications
Biometric Technology	FP (ZK): Touch-based optical fingerprint reader Highperformance live-finger detection Facial: Infrared light facial biometric that can identify user under 1 second
Audio	Speaker, Microphone
Soft Keypad	Capacitive Touch Screen
Modular & Technologies	Barcode badge reader: N/A (Can be added but need to meet MOQ) Magnetic stripe card reader: N/A(Can be added but need to meet MOQ) RFID: EM4100 SERIES PROX CARDS QR code reader <ul style="list-style-type: none"> PASSIVE PROX/RFID responder Multi-frequency card reader, Multi-Card supports all major RFID standards-for frequency ranges 125/134.2kHz and 13.56MHz, including NFC
Power	AC Power Adaptor: 12 V, 3.0A PoE (Power over Ethernet): PoE+ IEEE 802.3at Power Class Levels: 0~4 Maximum Current: 720mA Voltage Range(at PSE): 50~57V DC Maximum Power(at PES): 30W Input Voltage(at PD): 48V Maximum Power(at PD): 30W Battery: Voltage: 7.4V Capacity: 2000mAh Charge Voltage: 8.4V Normal Charge: 8hrs Fast Charge: 5hrs

© Copyright 2025. ZKTeco WFM is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved. Version 3.1