


The Best-In-Class Clock

Where the "P" Stands For Portable
And the 4G LTE Capability Makes It Possible



Workforce Data Collection Integration Flexibility



Specifications

Features	Technical Specifications
Processor	8-core
Display	<ul style="list-style-type: none"> 7" TFT LCD Capacitive Touch Screen 1024 x 600 Resolution 16:9.6 Aspect Ratio
System	Android OS
Memory	2GB RAM, 16GB ROM, micro SD card slot
Capacity	Fingerprint Module: 20,000 FAM33 Face Module: Visible light = 20,000; Near-infrared = 6,000 FAM33 Palm Module: Visible light = 5,000 Card: 10,000 Transaction: 1 Million
Communication	<ul style="list-style-type: none"> Standard 10/100/1000 Mbps Ethernet Certified Wi-Fi Dual Band 2.4G/5G, 802.11 a/b/g/n/ac USB 2.0 Ports Wiegand PTCRB Certified 4G LTE
Interface	<ul style="list-style-type: none"> LED module: 1 AUX Input: 2 Wiegand Input: 2 Relay: 2 (Alarm, Bell, External Lock) Programmable LED indicator: 2
Environment	Operating Temperature: 14° F to 131° F (-10° C to 55° C) Operating Humidity: 5% to 80% non-condensing
Dimensions	Width Base: 9.21 in. (23.4 cm) Width fully configured: 9.72 in. (24.7 cm) Height: 5.28 in. (13.4 cm) Depth: 2.38 in. (6.05 cm)

Features	Technical Specifications
Biometric Technology	FP (ZK): Touch-based optical fingerprint reader Facial: Infrared light facial biometric that can identify user in less than one second. Visible Light Recognition: V5.9 with FAM33 Module Palm: FAM33 Module - Palm Support, Visible Light
Audio	Speaker, Microphone
Soft Keypad	Capacitive Touch Screen
Readers & Supported Card Technologies	RFID: EM4100 SERIES PROX CARDS <ul style="list-style-type: none"> PASSIVE PROX/RFID responder Multi-frequency card reader; Multi-Card supports all major RFID standards for frequency ranges 125/134.2kHz and 13.56MHz, including NFC
Power	AC Power Adaptor: 12V, 1.5A PoE (Power over Ethernet): PoE+ IEEE 802.3at Power Class Levels: 0~4 Maximum Current: 720 mA Voltage Range (at PSE): 50~57VDC Maximum Power (at PES): 30W Input Voltage (at PD): 48V Maximum Power (at PD): 30W Battery: Voltage: 7.4V Capacity: 7600mAh Charge Voltage: 8.4V Normal Charge: 8hrs Fast Charge: 5hrs

© Copyright 2026. ZKTeco WFM is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved. v3.2 USW